

ARCHITECTS' & ENGINEERS' SPECIFICATIONS

High Power Two-way Full-range Speaker System

IF2205 (W)

The two-way full range loudspeaker system shall incorporate dual 5-inch low frequency transducers with 2-inch voice coil and a 1-inch-exit high frequency 1-inch compression driver mounted to a constant directivity horn. The HF horn shall be capable of being rotated to accommodate horizontal or vertical installation. The total system shall meet the following performance criteria: System frequency response shall vary no more than ± 3 dB from 85 Hz to 18 kHz measured on axis with appropriate signal processing. The loudspeaker shall produce a Sound Pressure Level (SPL) of 89 dB SPL on axis at 1 meter with a power input of 1 Watt, and shall be capable of producing a continuous output of 118 dB SPL and a peak output of 115 dB SPL on axis at 1 meter. The loudspeaker shall handle 100 Watts of amplifier power (2 hrs, IEC noise) and shall have a nominal impedance of 8 Ohms. Horizontal coverage of 90° between -6 dB points; Vertical coverage of 60° between -6 dB points. The loudspeaker enclosure shall be Rectangular in shape. It shall be constructed of 12 mm thick Finland birch plywood. It shall be finished in a black or white textured coating. Input connectors shall be barrier strip. A total of 6 x M8 and 2 x M6 threaded mounting point shall be provided. An internal passive frequency dividing network shall provide a 2nd order acoustic crossover for low and high frequency subsystems. The front of the loudspeaker shall be covered with a powder coated perforated steel grill backed with open cell foam to protect against dust. The two-way full range loudspeaker system shall be the YAMAHA IF2205 (W).